



1810 SAVOIE

CARACTERISTICS

- Organic glass lens
- Stainless steel mirror back
- Aerodynamic shape to reduce particle deposits and permit easy cleaning with water.
- Materials unaffected by corrosive atmosphere in tunnels
- Beams angled 45°
- Fireproof safety cable CR1-C1 optional

Fixing by sides ears (1810C)



| | |
|----------------|--|
| Number of LEDs | 24 |
| Type of LEDs | Wide angle 5 mm LEDs (H) |
| Color(s) | Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L) |

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:
<http://www.lec-lyon.com/1810z-savoie-r122>

APPLICATION

- ☒ Marker-lighting

CONFIGURATEUR.EMPLACEMENT

- ☒ Wall lights

CARACTERISTICS

Weight : 250 g

Options of luminous effects

- ☒ Non adjustable
- ☒ Inclined beam
- ☒ Paralell beam
- ☒ Transparent flat window

Power supply - Control

- ☒ Cable length: 1 m

Integrated : 24V-PWM
Remote : 24V-0/10V, 24V-DMX, 24V-DALI

Material

- ☒ Vandalism-proof, UV-proof, polycarbonate window

Mechanical strength - Waterproofness

- IP69 K** pressure water spray (previous registration)
- Certified in compliance with European Standards 60598-2-22 for emergency lighting units
- IK10 40J** Resists impacts up to IK10 40J
- IP67** Tight for temporary immersion