

1830XX **LUCERNE**

«Medium» version in the round flush recessed raking light range. Choice of lighting effects for customised LED marker-lighting.

APPLICATIONS:

- Decorative or safety markerlighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement


CARACTERISTICS

Beacon with specific signage LEC offers custom options


- · Anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1830K and 1830D)
- Withstands occasional traffic from all kinds of vehicles
- RGB options available



Votre visuel, personnalisable sur demande



Ø 61



Number of LEDs 36 Type of LEDs 120° SMD LEDs (S) Warm white 2700K (F), Warm white 3000K (E), Neutral Color(s) white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1830xxz-lucerne-r2628

APPLICATION

Marker-lighting

CONFIGURATEUR.EMPLACEMENT

Ground flush recessed fittings

Ground recessed fittings

Pavements sides

CARACTERISTICS

Weight: 290 g

Options of luminous effects



(1) Adjustable on 1 axis

Flat homogeneous window (optional)

Colour control system (optional)

Power supply - Control

Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Integrated: 230V-Non dimmable

Material

(AL) Anodised glazed aluminium

Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

Withstands random all vehicles traffic

IK10 Resists impacts up to IK10 60J

Tight for extended **IP68** immersion