

## 1570RH CHATEAUNEUF

«Medium» version in the round flush recessed raking light range. The flange hides recess plate imperfections.

### APPLICATIONS:

- Decorative or safety marker-lighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

### CARACTERISTICS

Uniform window

- Colourless anodised machined aluminium body (except 1570RX)
- Vandalproof organic glass window
- Recess in or attach to walls, bollards, poles or other supports



Number of LEDs	36, 12, 4
Type of LEDs	120° SMD LEDs (S), SMD trichro (A), Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), RVB (T), Royal blue (K)



Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

<http://www.lec-lyon.com/1570rhz-chateauneuf-r1017>

### APPLICATION

-  Marker-lighting





### CONFIGURATEUR.EMPLACEMENT

-  Wall recessed
-  Pavements sides



### CARACTERISTICS

Weight : 400 g



### Options of luminous effects

-  RGB options
-  Non adjustable
-  Flat homogeneous window (optional)
-  Colour control system (optional)

### Power supply - Control

-  Cable length: 1 m
-  **Integrated :** 24V-PWM  
**Remote :** 24V-0/10V, 24V-DMX, 24V-DALI

### Material

-  Anodised glazed aluminium
-  Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

### Mechanical strength - Waterproofness

- IK10** Resists impacts up to IK10
- 60J**
- IP68** Tight for extended immersion