

5640 SCHOOL-LIGHT

Spotlight recessed into custom-made stainless steel handrail Wide choice of lenses:

- Very extensive asymmetric versions to ensure beam uniformity with intervals of up to 7m.
- Tilted beam to have tilted output even when the product is installed vertically to hide the light source.





APPLICATIONS:

- Handrails
- Cycle paths and pedestrian paths lighting
- Roadway lighting

CARACTERISTICS

- Colourless anodised machined aluminium
- Vandalproof organic glass window
- Flush-recessed
- 316L Stainless steel handrail available on request (Ø48mm or 76mm). Other sizes are available on a made-to-measure basis
- RGB options available
- Colourless anodised machined aluminium
- Vandalproof organic glass window
- Flush-recessed
- 316L Stainless steel handrail available on request (Ø48mm or 76mm). Other sizes are available on a made-to-measure basis



| | |
|----------------|--|
| Number of LEDs | 6 |
| Type of LEDs | Power LEDs 1 Watt (B) |
| Color(s) | Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K) |

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

<http://www.lec-lyon.com/5640-school-light-r102>


APPLICATION



Standard flux : 518 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT



Wall recessed



Handrails

CARACTERISTICS

Weight : 300 g

Options of luminous effects



20° deflected beam (option)



Non adjustable



Beam with various openings



Transparent flat window



Colour control system (optional)

Power supply - Control



Cable length: 0.2 m



Integrated : 24V-PWM



Remote : 24V-0/10V, 24V-DMX, 24V-DALI

Material



Anodised glazed aluminium



Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness



IK10 Resists impacts up to IK10 20J



IP67 Tight for temporary immersion

5640 SCHOOL-LIGHT

This datasheet gives you all the available optics for this product, consistent with the number of LEDs.
 URL of this product: <http://www.lec-lyon.com/5640-school-light-r102>

