

5681MAM **LIMA**

Orientable linear LED spotlight, surface mounted, for uniform illumination of very high walls and facades. Its trapdoor compartment hides cabling and connectors.

APPLICATIONS:


- · Highlight architectural features,
- Facade, monument lighting
- Continuous line
- Tree and vegetation uplighting
- · Direct or indirect lighting of public space

CARACTERISTICS

Blue, white and red LEDs installed to reproduce the French flag.

- Colourless anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Thermolacquered paint on request
- 3 mounting pads available 2 versions (15cm or 30cm) and one version for belt-courses
- RGBW options available







APPLICATION



Outdoor lighting

Standard flux: 7136 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT



Wall lights

CARACTERISTICS

Weight: 4700 g

Options of luminous effects



(1) Adjustable on 1 axis



Transparent flat window

Power supply - Control

Cable length: 1 m

Integrated: 24V-Non dimmable

Integrated: 230V-Non dimmable

Material



(AL) Anodised glazed aluminium



Vandalism-proof, UV-proof, polycarbonate window

Mechanical strength - Waterproofness

IK10 Resists impacts up to IK10

Tight for temporary IP67 immersion

Number of LEDs

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5681mam-lima-r1274

32

OPTIC DATASHEET



5681MAM LIMA

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5681mam-lima-r1274

