

## 5655 **LIGNON**

Light bar can be ordered to lengt (max. 2m) for individual installation or as a continuous line for uninterrupted lighting. The product's polycarbonate and aluminium profiles are clipped together to allow for every possil product orientation. Cable outpu at the end of the fitting. Slightly diffusing polycarbonate window t avoid glare. Built-in groove to accommodate nuts to adjust the position of the mounting bracket Multiple types of installation possible: cornice, wall, handrail, integration into street furniture. etc. A wide choice of mounting brackets are also available. Minimum length = 100mm


#### **APPLICATIONS:**


- · Highlight architectural features.
- · Lighting from a cornice
- · Lighting under benches or handrails
- Continuous line

#### CARACTERISTICS

- Vandal-resistant diffusing polycarbonate window
- Colourless anodised aluminium sleeve with integrated groove for M4 nuts (fixing)
- Cable outlet in line with axis
- · Accessories: PF mounting brackets for cornice / PF1 adjustable / PF2 for facade
- RGB option available







# 120 120° SMD LEDs (S), 120° high intensity SMD LEDs (Z) Warm white 2700K (F), Warm white 3000K (E), Neutral

white 4000K (N), Cool white 6000K (W), Red (R), Amber (O),

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

Green (V), Blue (L)

http://www.lec-lyon.com/5655-lignon-r1305

Number of LEDs

Type of LEDs

Color(s)

#### **APPLICATION**



**Outdoor lighting** 

Standard flux: 1452 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

#### **CONFIGURATEUR.EMPLACEMENT**



Wall lights



#### CARACTERISTICS

Weight: 300 g/m

#### **Options of luminous effects**



**RGB** options



Non adjustable



Transparent flat window

#### **Power supply - Control**



Cable length: 0.2 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

#### Material



Anodised glazed aluminium

## Mechanical strength - Waterproofness

IK06 Resists impacts up to IK06

product.legend-**IP66** immersion.66

## **OPTIC DATASHEET**



### **5655 LIGNON**

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product:  $\frac{\text{http://www.lec-lyon.com/5655-lignon-r1305}}{\text{http://www.lec-lyon.com/5655-lignon-r1305}}$ 

