

2855 METEOR

«Maxi» version in the round flush recessed raking light range.

APPLICATIONS:

- Highlight architectural features, street furniture, landscapes...
- Uniform facade lighting
- Squares and public places

CARACTERISTICS

- Colourless anodised aluminium body and flange
- Vandalproof organic glass window
- 316L Stainless steel screws
- Installs in dedicated recess plate
- RGB options available



Number of LEDs	12
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:
<http://www.lec.fr/2855-meteor-r135>

APPLICATION

Outdoor lighting

Standard flux : **2676 lm**

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

- Ground flush recessed fittings
- Ground recessed fittings

CARACTERISTICS

Weight : **860 g**

Options of luminous effects

- RGB options
- 20° deflected beam (option)
- Non adjustable
- Beam with various openings
- Transparent flat window
- Colour control system (optional)

Power supply - Control

- Cable length: **1 m**
- Integrated** : 24V-PWM
Remote : 24V-0/10V, 24V-DMX, 24V-DALI
- Integrated** : 230V-Non dimmable, 230V-0/10V

Material

- AL** Anodised glazed aluminium
- PC 2** Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

- IK10** Resists impacts up to 60 joules (IK10)
- IP68** Tight for extended immersion

2855 METEOR

This datasheet gives you all the available optics for this product, consistent with the number of LEDs.

URL of this product: <http://www.lec.fr/2855-meteor-r135>

