

# 2855 **METEOR**

«Maxi» version in the round flush recessed raking light range.


## **APPLICATIONS:**


- · Highlight architectural features, street furniture, landscapes...
- Uniform facade lighting
- Squares and public places

## CARACTERISTICS

- · Colourless anodised aluminium body and flange
- Vandalproof organic glass window
- 316L Stainless steel screws
- · Installs in dedicated recess plate
- RGB options available







Number of LEDs	12
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/2855-meteor-r135

#### **APPLICATION**


Outdoor lighting

Standard flux: 2676 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

#### **CONFIGURATEUR.EMPLACEMENT**

Ground flush recessed fittings




#### CARACTERISTICS


Weight: 860 g


#### **Options of luminous effects**














#### **Power supply - Control**


Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Integrated: 230V-Non dimmable, 230V-0/10V

## Material

(AL) Anodised glazed aluminium



# **Mechanical strength - Waterproofness**

IK10 Resists impacts up to IK10 60J

Tight for extended IP68 immersion



# **2855 METEOR**

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/2855-meteor-r135

