4020
LUMINY 2

«Medium» version in the Luminy spotlight range.

Installs on roads/floors, wall or poles with custom-adaptable accessories.


APPLICATIONS:

- Highlight architectural features
- Highlight landscapes
- Path lighting, lanes, street furniture

CARACTERISTICS

- Colourless anodised machined aluminium body
- Vandalproof organic glass window
- 316L Stainless steel bracket and screws
- Thermolacquered bracket on request
- RGBW options available





Number of LEDs	4
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:
http://www.lec-lyon.com/4020-luminy-2-r137

APPLICATION

Outdoor lighting

Standard flux : **892 lm**
This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

Wall lights

Masts

CARACTERISTICS

Weight : **1070 g**

Options of luminous effects

RGBW option

Adjustable on 2 axis

Rotating beam

Beam with various openings

Transparent flat window

Colour control system (optional)

Power supply - Control

Cable length: **1 m**

Integrated : 24V-PWM
Remote : 24V-0/10V, 24V-DMX, 24V-DALI

Integrated : 230V-Non dimmable

Material

Anodised glazed aluminium

Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness


IK10 20J Resists impacts up to IK10 20J

IP67 Tight for temporary immersion


LED EXPERTS SINCE 1977
LYON

4020 LUMINY 2


This datasheet gives you all the available optics for this product, consistent with the number of LEDs.
URL of this product: http://www.lec-lyon.com/4020-luminy-2-r137




10




20




36




52




77




120




130x25° (L1)




116x44° (L2)




40x10° (L4)



130x25°D50° (L5)



116x44°D36° (L6)



100x20° (L7)