

# 5620 **BRUNEI**

Recessed lightbar for public spaces. Length on request (max = 2000mm, min = 150mm), can be installed individually or as a continuous line. Clips in with no screws for vandalproof installation.


## **APPLICATIONS:**

- Illuminated handrail
- Bridge deck lighting
- · Direct or indirect lighting of public space

#### CARACTERISTICS

- Vandalproof profiled organic
- Colourless anodised aluminium profile (except 5620X)
- Recessed
- 2 Profiled mounts with extruded-aluminium accessories for continuous line or individual installation.
  - Ground-recessed version with internal space for running cable and connectors
  - Compact surface-mounted
- Version RGB options available





Number of LEDs	120
Type of LEDs	120° SMD LEDs (S), 120° high intensity SMD LEDs (Z)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5620-brunei-r141

#### **APPLICATION**

Outdoor lighting

Standard flux: 1452 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

#### **CONFIGURATEUR.EMPLACEMENT**

Wall lights

Wall recessed

Ground flush recessed fittings

Ground recessed fittings

Pavements sides

#### **CARACTERISTICS**

Weight: 730 g/m

#### **Options of luminous effects**



(x) Non adjustable

Beam with various openings

Transparent flat window

Colour control system

(optional)

## **Power supply - Control**

Cable length: Connector

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

### Material

(AL) Anodised glazed aluminium

Vandalism-proof organic

#### **Mechanical strength - Waterproofness**

Withstands 2-wheels traffic

Withstands random all vehicles traffic

IK10 Resists impacts up to IK10

Tight for extended IP68 immersion




## **5620 BRUNEI**

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5620-brunei-r141

Schéma optique à venir





45