

# 1830PMR **LUCERNE**

«Medium» version in the round flush recessed raking light range. Choice of lighting effects for customised LED marker-lighting.

# **APPLICATIONS:**

- Decorative or safety markerlighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement


## CARACTERISTICS

Beacon with specific PRM area signage LEC offers custom options

- · Anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1830K and 1830D)

Withstands occasional traffic from all kinds of vehicles







Number of LEDs	36
Type of LEDs	120° SMD LEDs (S)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1830pmrz-lucerne-r2429

## **APPLICATION**

Marker-lighting

#### **CONFIGURATEUR.EMPLACEMENT**

Ground flush recessed fittings

Ground recessed fittings

Pavements sides

#### **CARACTERISTICS**

Weight: 290 g

#### **Options of luminous effects**

**RGB** options



(1) Adjustable on 1 axis



Flat homogeneous window



Colour control system (optional)

#### **Power supply - Control**

Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Integrated: 230V-Non

## Material

(AL) Anodised glazed aluminium

Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

# **Mechanical strength - Waterproofness**



Technical data is subject to changes. Luminaire guaranteed 5 years.

Withstands random all vehicles traffic

IK10 Resists impacts up to IK10 60J

Tight for extended **IP68** immersion