

5781 **PASSY**

Linear spotlight for recessing in public spaces. Can be ordered in two lengths, installed individually or as a continuous line. Externally adjustable tiltable LED plate (0° to 25°) without without opening the fitting or compromising its water resistant. Device swivels in its recess for the opposite direction. Clips in with no screws for vandalproof installation.

APPLICATIONS:


- Medium height facade lighting (10m)
- Highlight architectural features, street furniture, trees...
- · Squares and public spaces

CARACTERISTICS

Length = 1 m

- Colourless anodised aluminium body
- Vandalproof organic glass window
- Flush-recessed
- Extruded aluminum profiled recess plate and accessories for continuous line or independent installation
- Cavity in the recess for running the cable and connectors
- Withstands occasional traffic from all kinds of vehicles
- RGBW options available
- anti-glare option available





Number of LEDs	32
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5781-passy-r2432

APPLICATION



Outdoor lighting

Standard flux: 7136 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

Ground flush recessed fittings

Ground recessed fittings


CARACTERISTICS

Weight : 6000 g


Options of luminous effects




RGBW option








Transparent flat window





Power supply - Control

Cable length: 1 m

Integrated: 230V-Non dimmable, 230V-0/10V, 230V-DMX, 230V-DALI

Material

(AL) Anodised glazed aluminium

Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2


Mechanical strength - Waterproofness

Withstands random all vehicles traffic

Resists compression up to 4 tons

IK10 Resists impacts up to IK10 60J 60J

Tight for extended IP68 immersion





5781 PASSY

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5781-passy-r2432

