

2855M **METEOR**

«Maxi» version in the round flush recessed raking light range.

APPLICATIONS:


- · Decorative or safety markerlighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement


CARACTERISTICS

Infinite mirror effect

- Colourless anodised aluminium body and flange
- Vandalproof organic glass window
- 316L Stainless steel screws
- Installs in dedicated recess plate
- RGB options available







APPLICATION

Marker-lighting

Ground flush recessed

fittings

Ground recessed fittings

CONFIGURATEUR.EMPLACEMENT

CARACTERISTICS

Weight: 590 g

Options of luminous effects

(x) Non adjustable



Transparent flat window

Power supply - Control

Cable length: 1m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Integrated: 230V-Non

dimmable

Material



(AL) Anodised glazed aluminium

Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

IK10 Resists impacts up to IK10

60J 60J

IP68 Tight for extended immersion

Number of LEDs	42
Type of LEDs	120° SMD LEDs (S)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/2855mz-meteor-r2451