

## 5629 BELVAL

Handrail spotlight with invisible-screw recessing unit Wide choice of lenses including:  
Very extensive asymmetric versions to ensure beam uniformity with intervals of up to 7m  
Tilted beam to have tilted output even when the fitting is installed vertically to hide the light source

### APPLICATIONS:

- Cycle paths and pedestrian paths lighting
- Roadway lighting
- Handrail
- Footbridge

### CARACTERISTICS

"Mini" version with 3 LEDs

- Colourless anodised machined aluminium body
- Vandalproof organic glass window
- Flush-recessed
- 2 possible recess profiles
- Colourless anodised machined aluminium body
- Vandalproof organic glass window
- Flush-recessed
- 2 possible recess profiles



Number of LEDs	3
Type of LEDs	Power LEDs 1 Watt (B)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:  
<http://www.lec-lyon.com/5629-belval-r2511>

### APPLICATION



Outdoor lighting

Standard flux : 259 lm

*This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)*

### CONFIGURATEUR.EMPLACEMENT



Wall recessed



Handrails

### CARACTERISTICS

Weight : 200 g

### Options of luminous effects



20° deflected beam (option)



Non adjustable



Beam with various openings



Transparent flat window

### Power supply - Control



Cable length: 0.2m



**Integrated :** 24V-PWM  
**Remote :** 24V-0/10V, 24V-DMX, 24V-DALI

### Material



Anodised glazed aluminium



Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

### Mechanical strength - Waterproofness



Resists impacts up to IK10 20J



Tight for temporary immersion

## 5629 BELVAL

This datasheet gives you all the available optics for this product, consistent with the number of LEDs.

URL of this product: <http://www.lec-lyon.com/5629-belval-r2511>

