

5751 **CLEM-IN**

Linear recessed projector for public spaces.

Orderable in 4 lengths, it allows individual continuous line or installations.

With the very extensive asymmetrical optics, homogeneous lighting is obtained even for a grazing installation.

Anti-vandalism installation clipping (no screw).

CARACTERISTICS

Length with recess = 1980mm

Vandal-proof organic glass profile Clear anodized aluminum sheath Without protrusion Cable outlet on the underside 24 LED 700mA controlled in PWM Four-color option possible: 4x16 350mA LED controlled in PWM





Number of LEDs	24
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5751-clem-in-r2514

APPLICATION




Outdoor lighting

Standard flux: 5352 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT

Ground flush recessed fittings




CARACTERISTICS


Weight: 1300 g


Options of luminous effects











Power supply - Control

Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Material

(AL) Anodised glazed aluminium

Vandalism-proof organic

Mechanical strength - Waterproofness

Withstands ran vehicles traffic Withstands random all

IK10 Resists impacts up to IK10

Tight for temporary



5751 CLEM-IN

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5751-clem-in-r2514

