

# 5753 **CLEM-IN**

Linear recessed projector for public spaces.

Orderable in 4 lengths, it allows individual continuous line or installations.

With the very extensive asymmetrical optics, homogeneous lighting is obtained even for a grazing installation.


Anti-vandalism installation by clipping (no screw).

#### CARACTERISTICS

Length with recess = 1020mm

Vandal-proof organic glass profile Clear anodized aluminum sheath Without protrusion Cable outlet on the underside 12 LEDs 700mA controlled in PWM Four-color option possible: 4x8 350mA LEDs controlled in PWM







Number of LEDs	12
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5753-clem-in-r2516

#### **APPLICATION**



Outdoor lighting

Standard flux: 2676 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

#### **CONFIGURATEUR.EMPLACEMENT**

Ground flush recessed fittings

Ground recessed fittings


### CARACTERISTICS

Weight: 750 g

#### **Options of luminous effects**



(X) Non adjustable



Transparent flat window

Colour control system (optional)

### **Power supply - Control**

Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

### Material

(AL) Anodised glazed aluminium

Vandalism-proof organic

# **Mechanical strength - Waterproofness**

Withstands ran vehicles traffic Withstands random all

IK10 Resists impacts up to IK10

Tight for temporary



## **5753 CLEM-IN**

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5753-clem-in-r2516

