

## 1570RHXX CHATEAUNEUF

«Medium» version in the round flush recessed raking light range. The flange hides recess plate imperfections.

### APPLICATIONS:

- Decorative or safety marker-lighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

### CHARACTERISTICS

Beacon with specific signage  
LEC offers custom options

- Colourless anodised machined aluminium body (except 1570RX)
- Vandalproof organic glass window
- Recess in or attach to walls, bollards, poles or other supports
- Withstands occasional traffic from all kinds of vehicles
- RGB options available



Votre visuel,  
personnalisable sur demande

Your image,  
customizable on demand

Number of LEDs	36
Type of LEDs	120° SMD LEDs (S)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L)



Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

<http://www.lec-lyon.com/1570rhxxz-chateauneuf-r2630>

### APPLICATION

-  Marker-lighting





### CONFIGURATEUR.EMPLACEMENT

-  Wall recessed
-  Pavements sides



### CHARACTERISTICS

Weight : 400 g



### Options of luminous effects

-  RGB options
-  Non adjustable
-  Flat homogeneous window (optional)
-  Colour control system (optional)

### Power supply - Control

-  Cable length: 1 m
-  **Integrated :** 24V-PWM  
**Remote :** 24V-0/10V, 24V-DMX, 24V-DALI

### Material

-  Anodised glazed aluminium
-  Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

### Mechanical strength - Waterproofness

- IK10** Resists impacts up to IK10
- 60J** 60J
- IP68** Tight for extended immersion