

1570RHXX **CHATEAUNEUF**

«Medium» version in the round flush recessed raking light range. The flange hides recess plate imperfections.

APPLICATIONS:

- Decorative or safety markerlighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

CARACTERISTICS

Beacon with specific signage LEC offers custom options

- Colourless anodised machined aluminium body (except 1570RX)
- Vandalproof organic glass window
- Recess in or attach to walls, bollards, poles or other supports
- Withstands occasional traffic from all kinds of vehicles
- RGB options available



Number of LEDs	36
Type of LEDs	120° SMD LEDs (S)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1570rhxxz-chateauneuf-r2630

APPLICATION



Marker-lighting

CONFIGURATEUR.EMPLACEMENT



Wall recessed



Pavements sides

CARACTERISTICS

Weight: 400 g

Options of luminous effects



RGB options



Non adjustable



Flat homogeneous window (optional)



Colour control system (optional)

Power supply - Control



Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Material



(AL) Anodised glazed aluminium



Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

IK10 Resists impacts up to IK10

60J 60J

Tight for extended IP68 immersion