

# 4330B **SAINT-JEAN**

Recessed spotlight for path lighting to be placed at less than one metre above ground.

Special H30 and H60 lenses Cycle paths and pedestrian paths lighting, at large intervals (more than 6m). Tiltable beam (+/-30°) without opening the spotlight.

Wall version of the 6430 bollard.


## **APPLICATIONS:**

- Cycle paths and pedestrian paths lighting
- Stair lighting
- Monuments lighting

#### **CARACTERISTICS**

- · Anodised aluminium body
- · Colourless anodised machined aluminium frame
- Vandalproof organic glass window
- Thermolacquered paint on frame on request





Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/4330b-saint-jean-r2681

### **APPLICATION**



**Outdoor lighting** 

Standard flux: 892 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

#### **CONFIGURATEUR.EMPLACEMENT**



Bollards

#### **CARACTERISTICS**

Weight: 8300 g

#### **Options of luminous effects**



faisceau incliné bas



(1) Adjustable on 1 axis



Beam with various openings



Transparent flat window

## **Power supply - Control**



Cable length: 1 m

Integrated: 24V-Non dimmable, 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Integrated: 230V-Non dimmable

#### Material



(AL) Anodised glazed aluminium



Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

## **Mechanical strength - Waterproofness**

IK10 Resists impacts up to IK10

Tight for temporary immersion



Adjustable orientation without dismantling