

# 4660 **CORSICA**

Spotlight developed for illuminating facades, with a compact design and optimised for uniform wall-washing.


# **APPLICATIONS:**

- · Facade, monument lighting
- Tree and vegetation uplighting
- Direct or indirect lighting of public space

# CARACTERISTICS

- · Aluminium body with thermolacquered paint finish, RAL on request
- Vandalproof organic glass window
- Fixed or adjustable arm (max 1m)
- Tilt adjustment: +/- 90° around the 2-way-locking ball & socket and +/- 15° around the arm axis
- Remote power & control unit (except 4661)
- · Optional light hood
- RGBW options available





Number of LEDs	42
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/4660-corsica-r462

# **APPLICATION**



Outdoor lighting

Standard flux: 9366 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

# **CONFIGURATEUR.EMPLACEMENT**

Wall lights



Masts

# **CARACTERISTICS**

Weight: 5000 g

# **Options of luminous effects**



RGBW option



(2) Adjustable on 2 axis



Rotating beam



Beam with various openings



Transparent flat window



Colour control system (optional)

# **Power supply - Control**



Cable length: 5 m

Integrated: 230V-Non dimmable, 230V-PWM, 230V-0/10V, 230V-DMX, 230V-DALI

# Material



Marine anodised cast aluminium



Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

# **Mechanical strength - Waterproofness**

IK10 Resists impacts up to IK10

20J 20J

Tight for temporary



# **4660 CORSICA**

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/4660-corsica-r462

