

## 1830M LUCERNE

«Medium» version in the round flush recessed raking light range. Choice of lighting effects for customised LED marker-lighting.


### APPLICATIONS:

- Decorative or safety marker-lighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

### CARACTERISTICS

Withstands occasional traffic from all kinds of vehicles

- Angled LED with internal mirror for 360° flush raking light.
- Anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1830K and 1830D)






|                |  |
|----------------|--|
| Number of LEDs | 16   |
| Type of LEDs   | Wide angle 5 mm LEDs (H)   |
| Color(s)       | Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L) |

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:  
<http://www.lec-lyon.com/1830mz-lucerne-r852>

### APPLICATION

-  Marker-lighting




### CONFIGURATEUR.EMPLACEMENT

-  Ground flush recessed fittings
-  Ground recessed fittings
-  Pavements sides




### CARACTERISTICS

Weight : 290 g



### Options of luminous effects

-  Adjustable on 1 axis
-  Inclined beam
-  Transparent flat window


### Power supply - Control

-  Cable length: 1 m
-  **Integrated :** 24V-PWM
-  **Remote :** 24V-0/10V, 24V-DMX, 24V-DALI

### Material

-  Anodised glazed aluminium
-  Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

### Mechanical strength - Waterproofness

-  Withstands random all vehicles traffic
- IK10** Resists impacts up to IK10
- 60J** 60J
- IP68** Tight for extended immersion