

# 5533 **SOULARY**

Cable-suspended spotlight for street lighting.

Orientable beam (+/-10°) without opening the spotlight and without compromising its water resistance.


## **APPLICATIONS:**

- Cycle paths and pedestrian paths lighting
- Public space lighting

## CARACTERISTICS

- · Colourless anodised machined aluminium body
- Aluminium cap with thermolacquered paint finish, RAL of your choice
- Vandalproof organic glass window





Number of LEDs	6
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5533-soulary-r876

#### **APPLICATION**



Outdoor lighting

Standard flux: 1338 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

#### **CONFIGURATEUR.EMPLACEMENT**



Overhead catenary lights

#### **CARACTERISTICS**

Weight : **1100** g

#### **Options of luminous effects**



**RGB** options



(1) Adjustable on 1 axis



Rotating beam



Beam with various openings



Transparent flat window



Colour control system (optional)

#### **Power supply - Control**



Cable length: 1 m

Integrated: 48V-PWM
Remote: 48V-0/10V, 48V-DMX, 48V-DALI

#### Material



(AL) Anodised glazed aluminium



Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

#### **Mechanical strength - Waterproofness**

IK10 Resists impacts up to IK10

Tight for temporary IP67 immersion



# **5533 SOULARY**

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5533-soulary-r876

