

1750K BOURGOGNE

«Mini» version in the round flush recessed raking light range. Choice of lighting effects for customised marker-lighting. RGB options available.


APPLICATIONS:

- Decorative or safety marker-lighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

CARACTERISTICS

The flange (3mm) hides recess plate imperfections. Colourless anodised machined aluminium body

- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1750K and 1750DS)
- 3 possible recess dimensions
- Withstands occasional traffic from all kinds of vehicles (1750 & 1750H)



| | |
|----------------|---|
| Number of LEDs | 3 |
| Type of LEDs | 120° SMD LEDs (S), SMD trichro (A) |
| Color(s) | Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), RVB (T) |

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

<http://www.lec-lyon.com/1750kz-bourgogne-r907>

APPLICATION

- Marker-lighting

CONFIGURATEUR.EMPLACEMENT

- Ground recessed fittings

CARACTERISTICS

Weight : 150 g

Options of luminous effects

- RGB options
- Non adjustable
- Transparent flat window
- Colour control system (optional)

Power supply - Control

- Cable length: 1 m
- Integrated : 24V-PWM
Remote : 24V-0/10V, 24V-DMX, 24V-DALI

Material

- Anodised glazed aluminium
- 316L Stainless steel
- Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

- Resists impacts up to IK10 20J
- Tight for extended immersion