# **PRODUCT DATASHEET**



## APPLICATION Marker-lighting CONFIGURATEUR.EMPLACEMENT Ground flush recessed 💷 fittings Ground recessed fittings Pavements sides CARACTERISTICS Weight : 290 g **Options of luminous effects RGB** options (1) Adjustable on 1 axis Transparent flat window Colour control system (optional) **Power supply - Control** ᠵ Cable length: 1 m Integrated : 24V-PWM Remote : 24V-0/10V, 24V-DMX, 24V-DALI $\langle \hat{\mathbf{n}} \rangle$ Integrated: 230V-Non dimmable Material (AL) Anodised glazed aluminium Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2 **Mechanical strength - Waterproofness** Withstands random all



IP68 Tight for extended immersion

### 1830 LUCERNE

«Medium» version in the round flush recessed raking light range. Choice of lighting effects for customised LED marker-lighting.

#### APPLICATIONS:

- Decorative or safety markerlighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

#### CARACTERISTICS

- Anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1830K and 1830D)


Withstands occasional traffic from all kinds of vehicles

• RGB options available



Ø 105

Ø 61



Number of LEDs	36, 12
Type of LEDs	120° SMD LEDs (S), SMD trichro (A)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), RVB (T)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link: http://www.lec-lyon.com/1830z-lucerne-r909

Technical data is subject to changes. Luminaire guaranteed 5 years. Luminaire designed and manufactured in France.