

# 1830H **LUCERNE**

«Medium» version in the round flush recessed raking light range. Choice of lighting effects for customised LED marker-lighting.

# **APPLICATIONS:**

- Decorative or safety markerlighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

## CARACTERISTICS


Uniform window

- Anodised aluminium body
- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1830K and 1830D)

Withstands occasional traffic from all kinds of vehicles

• RGB options available





Number of LEDs	36, 12, 4
Type of LEDs	120° SMD LEDs (S), SMD trichro (A), Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), RVB (T), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/1830hz-lucerne-r910

## **APPLICATION**

Marker-lighting

#### **CONFIGURATEUR.EMPLACEMENT**

Ground flush recessed fittings

Ground recessed fittings

Pavements sides

#### **CARACTERISTICS**

Weight: 290 g

#### **Options of luminous effects**

**RGB** options

(1) Adjustable on 1 axis

Flat homogeneous window (optional)

Colour control system (optional)

## **Power supply - Control**

Cable length: 1 m

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Integrated: 230V-Non

## Material

(AL) Anodised glazed aluminium

Vandalism-proof, scratchproof, UV-proof, polycarbonate window, M2

## **Mechanical strength - Waterproofness**

Withstands random all vehicles traffic

IK10 Resists impacts up to IK10

60J

Tight for extended **IP68** immersion