

1570R CHATEAUNEUF

«Medium» version in the round flush recessed raking light range. The flange hides recess plate imperfections. For versions with recessed elements, see LUCERNE.



APPLICATIONS:

- Highlight architectural features, street furniture, landscape...
- Surface mounted lighting for cycle path, pedestrian path, stairs
- Squares and public places

CARACTERISTICS

- Colourless anodised machined aluminium body (except 1570RX)
- Vandalproof organic glass window
- Recess in or attach to walls, bollards, poles or other supports

Number of LEDs	4
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

<http://www.lec-lyon.com/1570r-chateauneuf-r923>


APPLICATION

Outdoor lighting


Standard flux : 892 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT



Wall recessed



Pavements sides

CARACTERISTICS

Weight : 400 g


Options of luminous effects



RGB options



20° deflected beam (option)




Non adjustable



Beam with various openings




Transparent flat window



Colour control system (optional)

Power supply - Control



Cable length: 1 m

 Integrated : 24V-PWM
 Remote : 24V-0/10V, 24V-DMX, 24V-DALI

Material



AL Anodised glazed aluminium



PC 2 Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

Mechanical strength - Waterproofness

 IK10 Resists impacts up to IK10
 60J 60J

 IP68 Tight for extended immersion

1570R CHATEAUNEUF

This datasheet gives you all the available optics for this product, consistent with the number of LEDs.
 URL of this product: <http://www.lec-lyon.com/1570r-chateauneuf-r923>

