

## 1750C2 BOURGOGNE

«Mini» version in the round flush recessed raking light range. Choice of lighting effects for customised marker-lighting. RGB options available.

### APPLICATIONS:

- Decorative or safety marker-lighting
- Installed at regular intervals to mark a path, cycle path, stairs
- Public space enhancement

### CARACTERISTICS

Dome emits a horizontal beam illuminating 120° in opposite directions. High output leds only. Colourless anodised machined aluminium body

- Vandalproof organic glass window
- 316L Stainless steel screws
- Flush-recessed (except 1750K and 1750DS)
- 3 possible recess dimensions
- Withstands occasional traffic from all kinds of vehicles (1750 & 1750H)



Number of LEDs	1
Type of LEDs	Power LEDs. Contact us for hot countries.
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), Royal blue (K)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:  
<http://www.lec.fr/1750c2z-bourgogne-r927>

### APPLICATION

- Marker-lighting

### CONFIGURATEUR.EMPLACEMENT

- Ground recessed fittings

### CARACTERISTICS

Weight : 200 g

### Options of luminous effects

- Non adjustable
- Paralell beam
- Transparent flat window

### Power supply - Control

- Cable length: 1 m
- Integrated** : 24V-PWM
- Remote** : 24V-0/10V, 24V-DMX, 24V-DALI

### Material

- AL Anodised glazed aluminium
- 316L 316L Stainless steel
- PC 2 Vandalism-proof, scratch-proof, UV-proof, polycarbonate window, M2

### Mechanical strength - Waterproofness

- Withstands random all vehicles traffic
- IK10 20J** Resists impacts up to 20 joules (IK10)
- IP68** Tight for extended immersion