

5620S **BRUNEI**

Recessed lightbar for public spaces. Length on request (max = 2000mm, min = 150mm), can be installed individually or as a continuous line. Clips in with no screws for vandalproof installation.

APPLICATIONS:


- Illuminated handrail
- Bridge deck lighting
- · Direct or indirect lighting of public space

CARACTERISTICS

Diffusing lighting

- Vandalproof profiled organic
- Colourless anodised aluminium profile (except 5620X)
- Recessed
- 2 Profiled mounts with extruded-aluminium accessories for continuous line or individual installation.
 - Ground-recessed version with internal space for running cable and connectors
 - Compact surface-mounted
- Version RGB options available





| Number of LEDs | 120 |
|----------------|--|
| Type of LEDs | 120° SMD LEDs (S), 120° high intensity SMD LEDs (Z) |
| Color(s) | Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L) |

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:

http://www.lec-lyon.com/5620s-brunei-r971

APPLICATION



Outdoor lighting

Standard flux: 1162 lm

This value is gained from the optimum output of the LED number, inclusive of optic, for a cool white LED (6000K)

CONFIGURATEUR.EMPLACEMENT



Wall recessed



Ground flush recessed fittings



Ground recessed fittings



Pavements sides

CARACTERISTICS

Weight: 730 g/m

Options of luminous effects



RGB options



xy Non adjustable




Beam with various openings



Flat frosted window





(optional)

Power supply - Control



Cable length: Connector

Integrated: 24V-PWM Remote: 24V-0/10V, 24V-DMX, 24V-DALI

Material



(AL) Anodised glazed aluminium



Vandalism-proof organic


Mechanical strength - Waterproofness



Withstands 2-wheels traffic



Withstands random all vehicles traffic



Tight for extended IP68 immersion




5620S BRUNEI

This datasheet gives you all the available optics for this product, consistent with the number of LEDs. URL of this product: http://www.lec-lyon.com/5620s-brunei-r971

Schéma optique à venir





45